

## SCALEOVIEW T17-2 17 Inch LCD TFT Display

Issue October 2005

Pages 2

Sleek, space-saving and full of visual innovation, the SCALEOVIEW T17-2 is the best choice TFT for families. It offers great performance for the home office and multimedia such as photo editing, gaming and viewing the latest DVDs. With a generous display area, great picture quality and fast response times. It is the ideal TFT for those seeking upgrade their bulky CRT.

### Highlights

- Displays for differentiated demands
  - Office applications
  - Fast Internet and multimedia
  - Games are best supported
- Very easy and comfortable to use
  - Plug & Play
  - Auto-adjust
  - Easy-to-use menu

### Ergonomics

- Optimum flicker-free and distortion-free ergonomics
- Excellent colour purity
- Outstanding brightness uniformity
- Wide viewing angle (160° / 120°)
- High contrast (350:1)
- Space saving design

### Technical highlights

- 17" (43cm) LCD TFT Display
- Excellent contrast 350:1
- Wide viewing angel 160° / 120°
- High brightness 350 cd/m<sup>2</sup>
- Amazing response time 8ms (gtg)

### Reliability

- Low power consumption
- Multi-level power management
- Guaranteed quality and stability



Response Time



<b>Visible screen diagonal</b>	17 inch (43 cm)
<b>Graphics display</b> (dependent on graphics processor)	
Pixels	1280 x 1024
Pixels*	800 x 600
Pixels*	640 x 480
* expanded	
<b>Highest resolution</b>	1280 x 1024
<b>Text display</b> (dependent on graphics processor)	
Pixels (max. 75Hz)	720 x 400
<b>Picture size</b>	338 x 270 mm
<b>Colours</b>	16.2 million
<b>Pixel Pitch</b>	0.264 mm
<b>Frequencies</b>	
Horizontal	30 - 82 kHz
Vertical	55 - 76 Hz
<b>Brightness</b> (typical)	350 cd/m <sup>2</sup>
<b>Contrast</b> (typical)	350:1
<b>Viewing angle</b> (typical)	
Horizontal	160°
Vertical	120°
<b>Response time</b> (typical)	8ms
<b>Plug and Play</b>	VESA DDC2B
<b>Setting options</b>	
Brightness (Back light)	
Contrast	
Picture position (horizontal and vertical)	
Color temperature and individual color setting	
Auto-adjust (direct access key)	
Auto balance	
Activate factory settings	
Menu language	
<b>Base</b>	
Tilt angle	-0°/ +20 °

<b>Electrical values</b>	
Rated voltage	100 - 240 V
Frequency	50 - 60 Hz
Power draw	
Max.	51 W
Stand by	2 W
Protection class	1
<b>Temperatures/dimensions/weight</b>	
Ambient temperature (to IEC721)	
Working	5°C to 35°C
Storage	-20°C to 60°C
Dimensions (H x W x D)	391 x 386 x 208 mm
(With Stand)	
Weight (Monitor only)	3.2 kg
<b>Reliability</b>	
MTBF (demonstrated)	70,000 h
Lifetime of LCD backlight	50,000 h
(brightness > 50 % of original brightness)	
<b>Compliance with standards</b>	
Product safety	EN60950
Ergonomics	GS mark ISO13406-2 (Pixel fault class II)
Radiation immunity and RFI suppression	CE certification according to EC Directive 89/336/EEC (EN55022/B, EN55024 EN61000-3-2/-3); TCO'99
<b>Video input</b>	1 x D-SUB analog
<b>Data cable (1.8 m)</b>	D-SUB (15-pin)
detachable on display	
<b>Power cable (1.8 m)</b>	For wall socket Euro-Schuko-Type CEE7
External power adapter	
Plug type on power adapter	IEC-320-C13
<b>Special features</b>	Standardized mounting interface according VESA FPMPI (75 mm)
<b>Order code</b>	S26361-K1012-V170 EAN: 4040528887666

