

Flat-type Ethernet Switches

	Unmanaged PoE+	Unmanaged
Model	WGS-804HP	WGS-803

Product Image



Hardware	LCD	-	-
	10/100/1000BASE-T	8	8
	1000 mini-GBIC	-	-
	100BASE-FX	-	-
Power	Switch Fabric	16Gbps	16Gbps
	Inputs	Dual 48~56V DC	12~48V DC or 24V AC
	Connector	3-pin terminal block, DC socket	3-pin terminal block, DC socket
	Consumption	140 watts	6 watts
Mechanical	Dimensions (W x D x H)	148 x 25 x 134 mm	148 x 25 x 134 mm
	Enclosure	IP30 metal	IP30 metal
	Mounting	DIN-rail, wall-mountable and magnetic wall mount	
Environment	Operating Temperature	-40~75 degrees C	-10~60 degrees C
	Operating Humidity	5% to 95%RH (non-condensing)	5% to 95%RH (non-condensing)
Regulatory	Emissions	FCC Class A, CE Class A	
	Stability	IEC60068-2-32 (Free Fall), IEC60068-2-27 (Shock), EC60068-2-6 (Vibration)	

Industrial Wireless AP Controller and PoE Router

Industrial Wall-mount Design Perfect for Public Facilities

PLANET WGR-500-4PV and WGR-500-4P AP Controller PoE Router with LCD Touch Screen, designed to be installed in a wall enclosure or simply mounted on a wall at any convenient location, features 4-port 10/100/1000BASE-T Gigabit Ethernet with IEEE 802.3at PoE+ and 1-port 100/1000BASE-T Gigabit Ethernet. It offers Layer 3 dynamic IP (DHCP Client), static IP, PPPoE, L2TP, PPTP..., intelligent Layer 2 and Layer 4 management functions, and user-friendly interface. They are able to operate reliably, stably and quietly in any environment without affecting its performance. The WGR-500 series is an ideal solution to meet the demand for the following network applications:

- Building/Home automation network
- Internet of things (IoT)
- IP surveillance
- Wireless LAN

The WGR-500 Series, with the Wireless AP Controller system, enables a small or medium wireless network to be simultaneously configured to minimize deployment time, effort and cost. No expensive instruments or complex back-end subscriber managed systems are required for deployment, thus bringing convenience to system administrators or machine operators.

	Touch LCD	Managed PoE+
Model	WGR-500-4PV	WGR-500-4P

Product Image




Hardware	LCD	2.4" Color TFT Touch Screen	-
	10/100/1000BASE-T	5 (4 LAN, 1 WAN)	
	Inputs	Dual 48~56V DC	
	Connector	3-pin terminal block, DC socket	
Mechanical	Dimensions (W x D x H)	180 x 25 x 140 mm	
	Enclosure	IP30 metal	
	Mounting	DIN-rail, wall-mountable and magnetic wall mount	
Environment	Operating Temperature	-10~60 degrees C	
	Operating Humidity	5% to 95%RH (non-condensing)	
Regulatory	Emissions	FCC Class A, CE Class A	
	Stability	IEC60068-2-32 (Free Fall), IEC60068-2-27 (Shock), EC60068-2-6 (Vibration)	
PoE	PoE Standard	802.3at PoE+	802.3at PoE+
	PoE Port	4	4
	PoE Budget	120 watts	120 watts
	PSE Type	End-sapn	End-sapn
Protocol	Power Pin Assignment	1/2(+), 3/6(-)	1/2(+), 3/6(-)
	VLAN	IEEE 802.1Q VLAN/Q-in-Q/Private VLAN/Protocol-based VLAN/Voice VLAN/GVRP	
Management	Interface	Web	Web
	SNMP	v1, v2c	v1, v2c
	System Log	System log and remote Syslog	



ERPS Ring for MAN Application
Recovery Time < 20ms

All-New Industrial Flat-type Ethernet

Perfect IP Network Deployment for Buildings and Factories



11F, No 96, Minquan Rd., Xindian Dist., New Taipei City 231, Taiwan (R.O.C.)
Tel: +886-2-2219-9518 Fax: +886-2-2219-9528 E-mail: sales@planet.com.tw
PLANET reserves the right to change specifications without prior notice. All brand names and trademarks are property of their respective owners. © PLANET Technology Corporation DM-Flat0618

Flat-type Ethernet Switches



Flat-type Ethernet Switches



Security Building Automation Switches

Suitable for buildings where security is strictly to be enforced, PLANET Industrial Wall-mount Managed Switches offer a comprehensive Layer 2 to Layer 4 Access Control List (ACL). The switches can restrict network access by denying packets based on source and destination IP address, TCP/UDP ports or defined typical network applications. The WGS-5225 Series incorporates advanced ITU-T G.8032 ERPS (Ethernet Ring Protection Switching) technology into customer's industrial automation network to enhance system reliability and uptime. With PLANET Industrial Wall-mount Managed Switches, a tightly-controlled network can be easily had in no time.

FTTx/MAN Application

PLANET Industrial Wall-mount Managed Switches adopt the double tag VLAN (Q-in-Q) technology to provide low cost and easy operation for service providers carrying traffic for multiple customers across their networks. With two dual-speed SFP slots built in, the deployment distance of PLANET Industrial Wall-mount Managed Switches can be extended up to 120 kilometers (single-mode fiber), which provides a high-performance edge service for FTTx solutions.

To build a network solution of FTTH (Fiber to the Home) or FTTC (Fiber to the Curb) for ISPs, and FTTB (Fiber to the Building) for enterprises, the various distances of SFP and BiDi (WDM) transceivers are optional for customers. For security and various applications, the 8 Gigabit ports of PLANET Industrial Wall-mount Managed Switches can be configured with VLAN settings and connected to different units, offices, floors, houses and departments.



Unique Flat-type Design with Touch LCD Screen or PoE Functions for Efficient Management

To facilitate the network deployment in any space-limited locations like wall enclosure or electric box found in buildings or outdoors, PLANET has the industrial Ethernet switches and wireless AP designed in a compact flat type. The products can be installed by fixed wall mounting, magnetic wall mounting or DIN rail, thereby making its usability more flexible. With the intuitive LCD Touch Screen or PoE Functions including PD alive check, scheduled power recycling, PoE schedule and PoE usage monitoring, PLANET's flat-type switches greatly promotes efficient and timely network management, perfectly suitable for surveillance, wireless and VoIP networks.



	Touch LCD		Managed PoE+			Managed	
Model	WGS-5225-8T2SV	WGS-5225-8P2SV	WGS-5225-8P2S	WGS-4215-8P2S	WGS-804HPT	WGS-4215-8T	WGS-4215-8T2S

Product Image



	LCD	2.4" Color TFT Touch Screen		-	-	-	-	-
Hardware	10/100/1000BASE-T	8	8	8	8	8	8	8
	1000 mini-GBIC	2	2	2	2	-	-	2
	100BASE-FX	Compatible	Compatible	Compatible	Compatible	-	-	Compatible
	Switch Fabric	20Gbps	20Gbps	20Gbps	20Gbps	16Gbps	16Gbps	20Gbps
Power	Inputs	12~48V DC or 24V AC	Dual 48~56V DC	Dual 48~56V DC	Dual 48~56V DC	Dual 48~56V DC	12~48V DC or 24V AC	12~48V DC or 24V AC
	Connector	3-pin terminal block, DC socket		3-pin terminal block, DC socket			3-pin terminal block, DC socket	
	Consumption	12 watts	251 watts	250 watts	210 watts	152 watts	10 watts	7.9 watts
Mechanical	Dimensions (W x D x H)	180 x 25 x 140 mm	180 x 25 x 140 mm	180 x 25 x 140 mm	178 x 25 x 134 mm	148 x 25 x 134 mm	148 x 25 x 134 mm	178 x 25 x 134 mm
	Enclosure	IP30 metal	IP30 metal	IP30 metal	IP30 metal	IP30 metal	IP30 metal	IP30 metal
	Mounting	DIN-rail, wall-mountable and magnetic wall mount						
Environment	Operating Temperature	-20~70 degrees C		-40~75 degrees C			-40~75 degrees C	
	Operating Humidity	5% to 95%RH (non-condensing)		5% to 95%RH (non-condensing)			5% to 95%RH (non-condensing)	
Regulatory	Emissions	FCC Class A, CE Class A		FCC Class A, CE Class A			FCC Class A, CE Class A	
	Stability	IEC60068-2-32 (Free Fall), IEC60068-2-27 (Shock), EC60068-2-6 (Vibration)						
PoE	PoE Standard	-	802.3at PoE+	802.3at PoE+	802.3af/802.3at	802.3af/802.3at	-	-
	PoE Port	-	8	8	8	4	-	-
	PoE Budget	-	240 watts	240 watts	200 watts	144 watts	-	-
	PSE Type	-	End-span	End-span	End-span	End-span	-	-
	Power Pin Assignment	-	1/2(+), 3/6(-)	1/2(+), 3/6(-)	1/2(+), 3/6(-)	1/2(+), 3/6(-)	-	-
Protocol	VLAN	IEEE 802.1Q VLAN/Q-in-Q/Private VLAN/Protocol-based VLAN/Voice VLAN/GVRP						
	IGMP Snooping	v2/v3/query	v2/v3/query	v2/v3/query	v2/v3/query	v2/v3/query	v2/v3/query	
	Spanning Tree	802.1w/802.1s	802.1w/802.1s	802.1w/802.1s	802.1w/802.1s	802.1w/802.1s	802.1w/802.1s	
	Data Redundancy	ERPS Ring RSTP/MSTP			RSTP/MSTP	RSTP/MSTP	RSTP/MSTP	RSTP/MSTP
	QoS	Port-based/802.1P/IP DSCP Policy-based/Voice VLAN						
	Security	802.1x, Static MAC, MAC filter, Port Security and IP Security						
Management	Traffic Control	In/out rate limit, storm control						
	Interface	Web, telnet, SSH and SSL						
	SNMP	v1, v2c, v3 and trap						
	System Log	System log and remote Syslog						